

MLSSA SPO 4.0D #960903-3057-3075

Measured Data

QC Limits

| Line | Parameter | Value | Units |
|------|------------|--------|-----------------------------|
| 1 | RMSE-free | 0.60 | Ohms |
| 2 | Fs | 44.77 | Hz |
| 3 | Re | 6.53 | Ohms[dc] |
| 4 | Res | 58.18 | Ohms |
| 5 | Qms | 3.89 | |
| 6 | Qes | 0.44 | |
| 7 | Qts | 0.39 | |
| 8 | L1 | 0.67 | mH |
| 9 | L2 | 1.01 | mH |
| 10 | R2 | 2.82 | Ohms |
| 11 | RMSE-load | 0.85 | Ohms |
| 12 | Vas(Sd) | 125.80 | liters |
| 13 | Mms | 36.80 | grams |
| 14 | Cms | 343 | $\mu\text{M}/\text{Newton}$ |
| 15 | B1 | 12.44 | Tesla-M |
| 16 | SPLref(Sd) | 95.9 | dB[Re] |
| 17 | Rub-index | 0.01 | |

Method: Mass-loaded (40.00 grams)

Area (Sd): 510.71 sq cm

DCR mode: Measure (-0.08 ohms)

QC file: CLOSED

Analysis successful. Shift in Fs = -31.0% (-20% to -50% is recommended).

MONACOR SP-12/100PA

MLSSA: Parameters