



---

Level (100:3507 Hz) = 99.00 dB SPL/watt (16 ohms, @1.50 meters)

---

KAPPA 15B 160HM

MLSSA: Frequency Domain



-74.67 dB, 2486 Hz (56), 4.180 msec (39)

DTTO

Measured Data

QC Limits

Line	Parameter	Value	Units
1	RMSE-free	0.94	Ohms
2	Fs	34.87	Hz
3	Re	10.82	Ohms[dc]
4	Res	220.96	Ohms
5	Qms	9.55	
6	Qes	0.47	
7	Qts	0.45	
8	L1	1.28	mH
9	L2	2.36	mH
10	R2	12.23	Ohms
11	RMSE-load	0.83	Ohms
12	Vas(Sd)	273.09	liters
13	Mms	78.36	grams
14	Cms	266	$\mu\text{M}/\text{Newton}$
15	B1	19.93	Tesla-M
16	SPLref(Sd)	95.8	dB[Re]
17	Rub-index	0.00	

Method: Mass-loaded (80.00 grams)

Area (Sd): 855.30 sq cm


DCR mode: Measure (-0.12 ohms)

QC file: CLOSED

Analysis successful. Shift in Fs = -29.3% (-20% to -50% is recommended).

EMINENCE KAPPA 15B 16OHM

MLSSA: Parameters



mean: 19.11, rms: 24.23, std: 14.89, max: 231.3, min: 11.01

MLSSA: Frequency Domain