



Applications:

Professional extra flex multipair cables with individually shielded and insulated pairs for mobile laying suitable for the realization of extensions or audio balanced multi-sockets or for connections of audio mixers and direction benches.

The flexibility and sturdiness give the possibility to wind and unwind the cable for several times without modifying the physical configuration and especially its technical features.

Characteristics:

Conductors: O.F.C. red copper
 Cond. Insulation: Solid PE
 Pair colours: White, Red
 Drain wire: O.F.C. tinned copper
 Pair Shields: Spiral covering 100%
 O.F.C. red copper
 Inner sheaths: PVC
 Ins. colours: Black and numbered
 Total Sheath: PVC
 Sheath colour: Black



tasker® Code	Cond. number	Nominal section AWG	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
C402	2x2	2 x 2 x 24 (0,22 mm ²)	28x0,10	1,0	3,0	9,0	100	B	9,5
C404	4x2	4 x 2 x 24 (0,22 mm ²)	28x0,10	1,0	3,0	10,2	100	B	12,5
C408	8x2	8 x 2 x 24 (0,22 mm ²)	28x0,10	1,0	3,0	13,0	100	B	23,0
C412	12x2	12 x 2 x 24 (0,22 mm ²)	28x0,10	1,0	3,0	16,0	100	B	35,0
C416	16x2	16 x 2 x 24 (0,22 mm ²)	28x0,10	1,0	3,0	17,0	100	B	41,5
C424	24x2	24 x 2 x 24 (0,22 mm ²)	28x0,10	1,0	3,0	19,0	100	B	61,0
C432	32x2	32 x 2 x 24 (0,22 mm ²)	28x0,10	1,0	3,0	24,0	100	B	77,0
C436	36x2	36 x 2 x 24 (0,22 mm ²)	28x0,10	1,0	3,0	26,0	100	B	95,0
C448	48x2	48 x 2 x 24 (0,22 mm ²)	28x0,10	1,0	3,0	27,0	100	B	115,0
C452	52x2	52 x 2 x 24 (0,22 mm ²)	28x0,10	1,0	3,0	28,0	100	B	124,0

WITHOUT TOTAL EXTERNAL SHIELD
FOR MOBILE INSTALLATION

Notes:

Conductor Resistance	Capacity Core/core	Capacity Core/shield
Ω/Km ± 5%	pF/mt	pF/mt
90	75	160
90	75	160
90	75	160
90	75	160
90	75	160
90	75	160
90	75	160
90	75	160
90	75	160
90	75	160
90	75	160
90	75	160
90	75	160
90	75	160
90	75	160
Velocity of propagation %	Max rated Voltage AC - V	Operative Temperature °C
66	49	-15 / +70