



Level (100:3018 Hz) = 92.05 dB SPL/watt (4 ohms, 01.00 meters)

DX12

MLSSA: Frequency Domain

MLSSA SPO 4.0D #960903-3057-3075 for Pro Dance Praha

Measured Data

QC Limits

Line	Parameter	Value	Units
1	RMSE-free	0.41	Ohms
2	Fs	60.48	Hz
3	Re	5.40	Ohms[dc]
4	Res	71.95	Ohms
5	Qms	6.64	
6	Qes	0.50	
7	Qts	0.46	
8	L1	0.89	mH
9	L2	1.54	mH
10	R2	5.06	Ohms
11	RMSE-load	0.46	Ohms
12	Vas(Sd)	65.55	liters
13	Mms	40.12	grams
14	Cms	173	$\mu\text{M}/\text{Newton}$
15	B1	12.85	Tesla-M
16	SPLref(Sd)	96.5	dB[Re]
17	Rub-index	0.01	

Method: Mass-loaded (50.00 grams)

Area (Sd): 520.00 sq cm

DCR mode: Measure (-0.29 ohms)

QC file: CLOSED

Analysis successful. Shift in Fs = -31.1% (-20% to -50% is recommended).

FANE DX 12 8 ohm

MLSSA: Parameters